

UT15B PRO/UT17B PRO are highly reliable, safe and durable true RMS multimeters with CAT III 1000V/CAT IV 600V ratings. Equipped with built-in VFC, it can filter interference, resulting in a more accurate voltage reading. These meters come with gold plated test leads for quick and accurate measurement. UT15B PRO/UT17B PRO also provide full range 1000V protection, as well as 8kV transient voltage protection, which can withstand sudden high voltage shocks.


Specifications	Range	UT15B PRO	UT17B PRO
Certificates	CE, UKCA, cETLus		
DC voltage (V)	1000V	$\pm(0.5\%+3)$	$\pm(0.5\%+3)$
AC voltage (V)	1000V	$\pm(1\%+3)$	$\pm(1\%+3)$
AC current (A)	10A	$\pm(1\%+3)$	$\pm(1\%+3)$
DC current (A)	10A	$\pm(0.8\%+3)$	$\pm(0.8\%+3)$
Resistance (Ω)	60M Ω	$\pm(0.5\%+2)$	$\pm(0.5\%+2)$
Capacitance (F)	6000 μ F	$\pm(2\%+5)$	$\pm(2\%+5)$
Frequency (Hz)	10Hz~100kHz		$\pm(0.1\%+3)$
Duty cycle	1%~99%		$\pm(1\%+4)$
Temperature ($^{\circ}$ C/ $^{\circ}$ F)	-55 $^{\circ}$ C~500 $^{\circ}$ C/-67 $^{\circ}$ F~932 $^{\circ}$ F		$\pm(2\%+1)$
Display count	6000		
AC frequency response	40~500Hz		
Category ratings	CAT III 1000V, CAT IV 600V		

Features	
VFC	Diode test
Auto range	Max/Min
Relative mode	Data hold
Flashlight	Low battery indication
True RMS	Auto backlight
Continuity test	Auto power off

Characteristics	
Standard accessories	English manual, test lead, temperature probe (UT17B PRO)
Power	1.5V battery (LR6) x 2
Display	66 x 51mm
Product size	195 x 95 x 58mm
Product net weight	UT15B PRO: 484g; UT17B PRO: 484g
Standard individual packing	Gift box, cloth bag
Standard quantity per carton	10pcs
Standard carton measurement	505 x 355 x 205mm
Standard carton gross weight	UT15B PRO: 8.8kg; UT17B PRO: 9.1kg



UT17B PRO



Gold plated test leads

